



COOPER INTERCONNECT  
CONNECTOR  
P/N: 26-159-24

8 x 0.1696" DIA MOUNTING HOLES  
FOR REQUIRED LENGTH NAS1352C8H  
FASTENERS OR 8-32 EQUIVALENT

MATERIAL: 6061-T6 ALUMINUM  
FINISH: PROBE BOOM: TITANIUM NITRADE (TiN)  
ON ELECTROLESS NICKEL  
ENCLOSURE: BLACK ANODIZED

2 x ANGLE-OF-ATTACK  
DIFFERENTIAL  
PRESSURE PORTS

TOTAL (PITOT)  
PRESSURE PORT

2 x SIDESLIP  
DIFFERENTIAL  
PRESSURE PORTS

8 x STATIC  
PRESSURE PORTS

REVERSE FLOW VENTILATION CHAMBER  
HOUSING FOR 0.039" DIA BEAD THERMISTOR  
AND RH SENSOR

TITLE PMS CANISTER TECHNICAL SPECIFICATIONS DRAWING				
DRAWN BY V. MANIVASAKAN	APPROVED BY B. WOODCOCK	DATE ISSUED 10 - 07 - 2013	MATERIAL SEE NOTES	FINISH SEE NOTES
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES AND METRIC DIMENSIONS IN BRACKETS [ ] TOLERANCES: TWO PLACE DECIMAL +/- 0.004 THREE PLACE DECIMAL +/- 0.001		THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF AVENTECH RESEARCH INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AVENTECH RESEARCH INC. IS PROHIBITED.		
DWG NO. PMSCANISTER-TSD			EDITION A	SHEET 1 OF 2