

ELECTRICAL


Operating Voltage: 12.5 - 37 VDC Input
Max. Operating Current: 85 mA typ. @ 12.5 VDC
Power: 1.1W typ. @ 12.5 VDC
Max. Output to CAN: 18W
Digital Interfaces: Controller Area Network (CAN2A), 500 kbps
RS-232 Serial Port (default 19.2 kbps)

RS232 Connector: Hirose HR30-6R-6P (6 Pin Male) Receptacle

Pin 1	TxD0
Pin 2	RxD0
Pin3	GND
Pin 4	TxD1
Pin 5	RxD1
Pin 6	GND

CAN Connector: Hirose HR30-6R-6S (6 Pin Female) Receptacle

Pin 1	SHIELD
Pin 2	PWR
Pin3	GND
Pin 4	CAN_H
Pin 5	CAN_L
Pin 6	NC

 Aventech <i>Research Inc.</i>	Aventech Research Inc. 110 Anne Street South, Unit 23 Barrie, Ontario, Canada L4N 2E3	TITLE CENTRAL PROCESSING MODULE (CPM) TECHNICAL SPECIFICATIONS
	THE INFORMATION CONTAINED IN THE SHEET IS THE SOLE PROPERTY OF AVENTECH RESEARCH INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AVENTECH RESEARCH INC. IS PROHIBITED.	REVISION A

Power Connector:

Hirose HR30-6R-3P (3 Pin Male) Receptacle

Pin 1 SHIELD

Pin 2 PWR (12.5 – 37 VDC)

Pin 3 GND

LED Indicators:

Power Green

Status 1 Bi-Colour Green/Red

Status 2 Bi-Colour Green/Red

PHYSICAL

Dimensions:

4.76 in. X 4.76 in. X 2.97 in.

(121.0 mm X 121 mm X 75.5 mm)

Weight:

1.46 lbs. (0.66 kg.)

ENVIRONMENTAL


Operating Temperature:

-20 C to 50 C

-40 C to 50 C (available under special order)

Storage Temperature:

-40 C to 90 C

	Aventech Research Inc. 110 Anne Street South, Unit 23 Barrie, Ontario, Canada L4N 2E3	TITLE CENTRAL PROCESSING MODULE (CPM) TECHNICAL SPECIFICATIONS
	THE INFORMATION CONTAINED IN THE SHEET IS THE SOLE PROPERTY OF AVENTECH RESEARCH INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AVENTECH RESEARCH INC. IS PROHIBITED.	REVISION A