

ELECTRICAL

Operating Voltage:	12.0 VDC nominal provided via CAN bus
Max. Operating Current:	300 mA typ. @ 12.0 VDC (OEMV-1 GPS Receiver)
Power:	3.6 W typ.
Digital Interfaces:	Controller Area Network (CAN2A), 500 kbps RS-232 Serial Port (default 19.2 kbps)
RS232 Connector:	Hirose HR30-6R-6P (6 Pin Male) Receptacle


Pin 1	TxD0
Pin 2	RxD0
Pin3	GND
Pin 4	PWR
Pin 5	GND
Pin 6	NC

CAN Connector:	Hirose HR30-6R-6S (6 Pin Female) Receptacle
----------------	---------------------------------------------

Pin 1	SHIELD
Pin 2	PWR
Pin3	GND
Pin 4	CAN_H
Pin 5	CAN_L
Pin 6	NC

GPS Antenna Connectors (Rear):	Tyco Electronics 221500-1 50 Ohm TNC Bulkhead Jack
--------------------------------	----------------------------------------------------

LED Indicators:	Power	Green
	Status 1	Bi-Colour Green/Red
	Status 2	Bi-Colour Green/Red

	Aventech Research Inc. 110 Anne Street South, Unit 23 Barrie, Ontario, Canada L4N 2E3	TITLE GPS PHASE MODULE (GPS) TECHNICAL SPECIFICATIONS
	THE INFORMATION CONTAINED IN THE SHEET IS THE SOLE PROPERTY OF AVENTECH RESEARCH INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AVENTECH RESEARCH INC. IS PROHIBITED.	REVISION A

PHYSICAL


Dimensions: 4.76 in. X 4.76 in. X 2.97 in.
(121.0 mm X 121 mm X 75.5 mm)

Weight: 1.58 lbs. (0.72 kg)

ENVIRONMENTAL

Operating Temperature: -40 C to 50 C

Storage Temperature: -40 C to 90 C

 Aventech Research Inc. 110 Anne Street South, Unit 23 Barrie, Ontario, Canada L4N 2E3	REVISION A	TITLE GPS PHASE MODULE (GPS) TECHNICAL SPECIFICATIONS
	THE INFORMATION CONTAINED IN THE SHEET IS THE SOLE PROPERTY OF AVENTECH RESEARCH INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AVENTECH RESEARCH INC. IS PROHIBITED.	DRAWING NUMBER AIMMS20-GPSV1