

## ELECTRICAL

---

Operating Voltage:	12.5 - 37 VDC Input
Max. Operating Current:	900 mA @ 12.5 VDC
Digital Interfaces:	Controller Area Network (CAN2A), 500 kbps

## ENVIRONMENTAL

---

Operating Temperature:	-20 C to 50 C
	-40 C to 50 C (available under special order)
	Storage Temperature:-40 C to 90 C
	RS-232 Serial Ports (default 19.2 kbps)

## PHYSICAL

---

Weight:	Varies from 12 lbs to 15 lbs depending on the application
---------	---

## WIND SPEED ACCURACY

---

Horizontal North and East Components:	0.50 m/s (1.0 knot) @ 150 knot TAS
Vertical:	0.75 m/s (1.5 knot) @ 150 knot TAS

## TEMPERATURE


---

Accuracy:	0.30 C
Resolution:	0.01 C

## RELATIVE HUMIDITY

---

Accuracy:	2.0%RH
Resolution:	0.1%RH
Broadcast / Log Update Rate:	1 - 10 Hz
Log Capacity:	45000 Records (12.5 hours @ 1 Hz)

	Aventech Research Inc. 110 Anne Street South, Unit 23 Barrie, Ontario, Canada L4N 2E3	TITLE PMS CANISTER TECHNICAL SPECIFICATIONS
	THE INFORMATION CONTAINED IN THE SHEET IS THE SOLE PROPERTY OF AVENTECH RESEARCH INC.. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF AVENTECH RESEARCH INC. IS PROHIBITED.	REVISION A